

# Lithium-sulfur battery positive electrode active materials

Why is sulfur a positive electrode active material for non-aqueous lithium batteries?

Sulfur (S) is considered an appealing positive electrode active material for non-aqueous lithium sulfur batteries because it enables a theoretical specific cell energy of 2600 Wh kg<sup>-1</sup> [1,2,3].

Are all-solid-state batteries with sulfur-based positive electrode active materials safe?

All-solid-state batteries with sulfur-based positive electrode active materials have been attracting global attention, owing to their safety and long cycle life. Li<sub>2</sub>S and S are promising positive electrode active materials for high energy density in these batteries because of high theoretical capacities.

Which active material is used in a positive electrode?

The sulfur active material used in the positive electrode exhibits a higher power density compared to the lithium sulfide active material employed in the electrode. However, the limited utilization of sulfur in the positive electrode is due to its low ionic and electronic conductivity.

Can lithium sulfide be used as active materials in lithium-sulfur batteries?

Traditionally, sulfur or lithium sulfide are conventionally utilized as active materials in lithium-sulfur batteries. To enhance the electronic and ionic conduction of active materials, it has been reported that coupling sulfur or lithium sulfide with solid electrolytes or various carbon materials can be effective.

Can a composite sulfur electrode be used in an all-solid-state lithium-sulfur battery?

J. Alloys Comput. 723, 787-794 (2017) Suzuki, K., Kato, D., Hara, K., et al.: Composite sulfur electrode prepared by high-temperature mechanical milling for use in an all-solid-state lithium-sulfur battery with a Li<sub>3.25</sub>Ge<sub>0.25</sub>P<sub>0.75</sub>S<sub>4</sub> electrolyte.

How to improve electrochemical performance of lithium sulfide active materials?

The homogeneous distribution of active materials and the presence of nano-sized particles are crucial for improving electrochemical performance. In order to achieve a homogeneous distribution and optimum particle size of the lithium sulfide active material on the cathode composite, compound approaches have always been heavily relied upon.

Lithium-based batteries are a class of electrochemical energy storage devices where the potentiality of electrochemical impedance spectroscopy (EIS) for understanding the battery charge storage ...

All-solid-state batteries with sulfur-based positive electrode active materials have been attracting global attention, owing to their safety and long cycle life. Li<sub>2</sub>S and S are promising positive electrode active materials for high energy density in these batteries because of high theoretical capacities.

# Lithium-sulfur battery positive electrode active materials

Nb 1.60 Ti 0.32 W 0.08 O 5-? as negative electrode active material for durable and fast-charging all-solid-state Li-ion batteries

Charge-discharge performance of all-solid-state Li/S batteries using several solid electrolytes to enhance energy density is investigated at 25 °C. The sulfur content in the positive composite electrode is 50 wt%. A correlation between the P/S ratio in a solid electrolyte and the reactivity of sulfur is observed.

One way of increasing the energy density of lithium-ion batteries is to use electrode materials that exhibit high capacities owing to multielectron processes. Here, we report two novel materials ...

Charge-discharge performance of all-solid-state Li/S batteries using several solid electrolytes to enhance energy density is investigated at 25 °C. The sulfur content in the ...

lithium sulfur batteries Ji Hwan Kim<sup>1,2,9</sup>, ... charge process for all three chalcogen positive electrode active materials, two prominent cathodic peaks were observed. The first cathodic peak ...

Hybrid composite cathode materials are applied to lithium-sulfur batteries. Electrochemical performance is influenced by intrinsic conductivity and volume expansion. ...

One of the most promising strategies to achieve high specific energy is constructing all-solid-state lithium metal batteries (ASSLMBs) by replacing the widely used graphite anode (372 mAh g ...

1 Introduction. Lithium-ion batteries, which utilize the reversible electrochemical reaction of materials, are currently being used as indispensable energy storage devices. [] One of the critical factors contributing to their widespread use is the significantly higher energy density of lithium-ion batteries compared to other energy storage devices. []

Sulfur (S) is considered an appealing positive electrode active material for non-aqueous lithium sulfur batteries because it enables a theoretical specific cell energy of 2600 Wh kg<sup>-1</sup> 1,2,3.

Due to its high theoretical specific capacity (1675 mAh g<sup>-1</sup>) and low cost, elemental sulfur is considered an ideal active material for lithium-sulfur batteries. In particular, the interface between sulfur and sulfide SSEs shows good chemical compatibility in sulfide-based ASSLSBs. Interestingly, sulfur materials were not used as the cathode ...

Recently, we developed a remarkable Li<sub>2</sub>S-based positive electrode active material: Li<sub>2</sub>S-Li<sub>2</sub>O-LiI. Particularly, Li<sub>2</sub>S- (66.7Li<sub>2</sub>O/33.3LiI) exhibited high capacity and long-term cycle performance.

Organic materials can serve as sustainable electrodes in lithium batteries. This Review describes the desirable characteristics of organic electrodes and the corresponding batteries and how we ...

# Lithium-sulfur battery positive electrode active materials

Sulfur utilization in high-mass-loading positive electrodes is crucial for developing practical all-solid-state lithium-sulfur batteries. Here, authors propose a low-density inorganic...

Due to its high theoretical specific capacity (1675 mAh g<sup>-1</sup>) and low cost, elemental sulfur is considered an ideal active material for lithium-sulfur batteries. In particular, ...

Web: <https://nakhsolarandelectric.co.za>

