

Does interlayer pressure affect the self-healing characteristics of metallized film capacitors?

Since the metallized film capacitor is a winding structure, the interlayer pressure has a certain influence on the self-healing characteristics of the metallized dielectric films. Chen pointed out that the capacitance loss of the winding MFC mainly occurs in the outer layer, and the pressure range in this area is  $<0.23$  MPa .

Does self-healing damage metallized polypropylene film capacitors?

Author to whom correspondence should be addressed. Self-healing (SH) in metallized polypropylene film capacitors (MPPFCs) can lead to irreversible damage to electrode and dielectric structures, resulting in capacitance loss and significant stability degradation, especially under cumulative SH conditions.

What happens if a metallized film capacitor is self-cleared?

During self-clearing of metallized film capacitors, there is a gradual decrease of capacitance as a result of an increasing number of self-clearing events, which eventually leads to catastrophic breakdown of the capacitor; for example, see Figure 4 B.

How good is self-healing dielectric elastomer actuator?

When a square-wave field of  $>17.2$  MV m<sup>-1</sup> was applied to the self-healing dielectric elastomer actuator after the introduction of mechanical damage, an area expansion of 3.6% was achieved, thereby indicating the excellent self-healing ability of the material at temperatures as low as  $-20\text{ }^\circ\text{C}$ .

How does self-clearing affect dielectric strength?

As a result of the self-clearing event, the damage site becomes electrically isolated from the applied electric field, limiting the adverse effects of the breakdown on the dielectric strength during further electrical cycling.

How does SH affect a capacitor?

Since SH occurs in a localized area of the capacitor for a very short time (us degree), it has less effect on the performance of the material in the non-self-healing region. It mainly results in capacitance loss of the capacitor component. Additionally, SH in capacitors is typically random.

We have developed a universal method for predicting the composition and evaluating the properties of the decomposition products obtained after the dielectric breakdown of a metallized film capacitor. This method applies to both existing and newly developed designs of capacitors.

Stretchable and self-healing light-emitting capacitors operating at low frequency and low voltage have been realized using a transparent elastomeric dielectric with high permittivity.

In this paper, the self-healing behaviors of the metallized high-temperature dielectric films of poly (ethylene 2,6-naphthalate) (PEN), poly (ether ketone) (PEEK) and ...

# Self-healing capacitor dielectric loss

Metal-film dielectric capacitors provide lump portions of energy on demand. While the capacities of various capacitor designs are comparable in magnitude, their stabilities make a difference. Dielectric breakdowns - micro-discharges - routinely occur in capacitors due to the inevitable presence of localized structure defects. The application of polymeric dielectric ...

The monitoring of the capacitor unit active power or dielectric loss tangent value over a period of time can determine the second type of self-healing failure to trigger the relay protection device to remove the fault capacitor to ...

Self-healing (SH) in metallized polypropylene film capacitors (MPPFCs) can lead to irreversible damage to electrode and dielectric structures, resulting in capacitance loss and significant stability degradation, especially ...

At this point, the polymer absorbed oxygen and generated insulating materials, which isolated the defective portion from the remainder of the capacitor. Despite the loss of some effective capacitance, the self-healing process had a negligible impact on the overall performance, while substantially reducing the LC [40, 41].

Due to the advantages of the high working reliability, low dielectric loss as well as light weight and the characteristic self-healing performance, metallized film capacitors (MFCs) are widely used in modern power electronic systems [1], [2], [3]. However, with the increasing demands in harsh environments such as inverters of hybrid and electric vehicles (140-150 ...

In this work, we utilize the broken translational symmetry in the crosslinked copolymers to reduce leakage current and conduction loss, leading to the dielectric polymers ...

self-healing capabilities and outlines novel research directions to tune the properties of self-healing. The capacitor consists of electrodes and a dielectric in between. Both of them respond to the electrical breakdown by losing their interatomic ...

In the context of the dielectric breakdown, self-healing designates a range of chemical processes, which spontaneously rearrange the atoms in the soot channels to partially return their insulative function. We developed a universal method capable of rating new capacitor designs including electrode and polymer material and their proportions. We ...

Due to the advantages of the high working reliability, low dielectric loss as well as light weight and the characteristic self-healing performance, metallized film capacitors (MFCs) are widely used in modern power electronic systems [1], [2], [3]. However, with the increasing demands in harsh environments such as inverters of hybrid and electric vehicles (140-150 ...

The monitoring of the capacitor unit active power or dielectric loss tangent value over a period of time can

# Self-healing capacitor dielectric loss

determine the second type of self-healing failure to trigger the relay protection device to remove the fault capacitor to achieve self-healing failure protection.

One approach to improve the damage tolerance of materials subjected to high electrical stress and operational lifetime is to provide a degree of self-healing. In this Perspective, we show that the majority of existing self-healing materials for such applications are polymer-based, in bulk monolithic or composite form.

Waveform diagram of element No. 3 in the process of self-healing failure test (a) Current waveform of element No. 3, (b) Active power curve on element No. 3, (c) The element No. 3 after test

In this paper, the self-healing behaviors of the metallized high-temperature dielectric films of poly (ethylene 2,6-naphthalate) (PEN), poly (ether ketone) (PEEK) and polyimide (PI) have been explored. Specifically, the influence of polymer chemistry, sheet resistance and interlayer pressure on self-healing process is analyzed in detail.

Web: <https://nakhsolarandelectric.co.za>

